



Montanari Group

GEARLESS&GEARBOX
TRACTION MACHINES

RANGE
M73

TOP
SELLER
480 kg
1 m/s
T.S. 480 mm



Carico Statico
Static Load
Charge Statique
Statische Belastung
Carga Estática

M73/M73B - 2200* kg
M73H - 2700 kg
M73S - 3200 kg
M73AL - 2500 kg

Motori
Motor
Moteurs
Motoren
Motores

VVVF 4 - 6 P
AC2 4/16 - 6/24 P

Peso Riduttore
Reductor Weight
Poids Reducteur
Getriebe Gewicht
Peso Reductor

M73/M73B/M73H - 110 kg
M73S - 115 kg
M73AL - 145 kg

Capacità Olio
Oil Capacity
Capacité Huile
Ölmenge
Capacidad Aceite

2.8 l

*Per tiro verso il basso - For downward roping - Mouflage vers le bas - Nach unten Zug - Tiro hacia abajo

Rapporti Ratio Rapport Übersetzung Reducción	Momento torcente Torque Moment Moment de Torsion Torsionsmoment Par de Torsion	Rendimento Efficiency Rendement Wirkungsgrad Rendimiento	
	Nm	1500/1800 RPM	1000/1200 RPM
1/75	750	0.58	0.54
1/60	940	0.71	0.68
1/52	809	0.73	0.70
1/46	1059	0.74	0.71
1/37	995	0.84	0.82
2/55	764	0.78	0.75
2/37	541	0.84	0.81

Telaio & Protezioni
Bedplate & Safety guards
Chassis & Protections
Maschinenrahmen & Seilschutzbügeln
Bancada & Protecciones #102-103


Gestisci il tuo argano con:
Manage your gearbox with:
Gérez votre treuil avec :
Verwalten Sie Ihre Getriebe mit:
Gestiona tu reductor con:

montanariapp


MORE ON
OUR WEBSITE



M73
M73H




DP	B	A
mm	mm	mm
≤600	115	105
650	78	117
700	87	120





(*)= according to motor size


M73AL



M73S



M73B



Momento Torcente Torque Moment Moment de Torsion Torsionsmoment Par de torsión	Voltaggio Voltage Tension Spannung Voltaje	Potenza Power Puissance Leistungen Potencia
Nm	V DC	W
800	207/104	352/88
Conforme a / Complies with / Conforme à / Entspricht / Conforme con: EN 81-20 ed EN 81-50		

